



TECHNOLOGY

Superconductor/Insulator Metal-Oxide Heterostructures for Electric Field Tunable Microwave Devices

OVERVIEW

It is desirable to have active circuit elements to be used in superconducting microwave device applications. Among various methods to modulate the microwave response of a circuit (i.e. obtain active response), the electric field induced modulation has clear advantages such as low energy consumption, input-output current isolation and high input resistance.

Metal-oxide superconductor/insulator heterostructures offer unique advantages over other structures for electric field induced modulation. Some of the advantages offered by this invention, developed by researchers at the University of Maryland, College Park, Department of Physics, include:

- High transition temperature and low carrier density for superconducting compounds such as $\text{YBa}_2\text{Cu}_3\text{O}_7$;
- High and tunable dielectric constant for insulating compounds such as SrTiO_3 ; and
- Physical and chemical compatibility of various heterostructure forms of these metal-oxides for easy device fabrication.

For more information, contact the Office of Technology Commercialization, 301-405-3947 or otc@umd.edu.

CONTACT INFO

UM Ventures
0134 Lee Building
7809 Regents Drive
College Park, MD 20742
Email: umdtechtransfer@umd.edu
Phone: (301) 405-3947 | Fax: (301) 314-9502

Additional Information

INSTITUTION

University of Maryland, College Park

PATENT STATUS

A U.S. patent, # 5,538,941, has issued

LICENSE STATUS

Available for non-exclusive license

EXTERNAL RESOURCES

UM-93-070